



## SPOT COOLERS

### PRODUCT SPECIFICATION:

**SS-40EG-8BTII / SS-40DG-8BTII**



<b>Model number</b>		<b>SS-40EG-8BTII</b>	<b>SS-40DG-8BTII</b>
<b>Automatic swivel</b>		No	Yes
<b>Power supply</b>		Single phase 220V,50Hz	
<b>Cooling capacity</b>		4.0 kW / 13,500 BTU	
<b>Compressor / output</b>		Air tight rotary model / 1.1 kW output	
<b>Air flow</b>	<b>Power output</b>	135 W	
	<b>Cool air volume</b>	10.5 m <sup>3</sup> / min (Strong) – 9.6 m <sup>3</sup> / min (Weak)	
	<b>Hot air volume</b>	19m <sup>3</sup> / min	
<b>Dimensions (mm)</b>		W 520 x D 470 x H 1120 (Not including hot / cold air ducts )	
<b>Operating condition</b>		25°C (50%) – 45°C (40%)	
<b>Drain tank capacity</b>		8 L	
<b>Electric cable length</b>		2 m	
<b>Power consumption</b>	1.90 kW	<b>Net weight</b>	73 kg
<b>Starting current</b>	40.0A	<b>Running current</b>	8.9 A
<b>Refrigerant</b>	R407C	<b>Refrigerant charge</b>	660 g
<b>Power factor</b>	97%	<b>Remarks</b>	All values are measured during operation in 35°C/ 60% humidity